

IN THE UNITED STATES PATENT & TRADEMARK OFFICE

TITLE:

DISPOSABLE URINE COLLECTION DEVICE

INVENTORS:

THERESA ERNEST and KIMBERLY L. TOMES

DISPOSABLE URINE COLLECTION DEVICE

Related Applications

[0001] This is a Continuation-in-Part of co-pending U.S. Application Serial No. 10/302,058 filed November 22, 2002.

Field of the Invention

[0002] The present invention relates generally to portable urinary devices. The present invention relates more specifically to a self-contained disposable urine collection device which allows comfortable and hygienic urination.

Description of the Related Art

[0003] In our highly mobile society, people sometimes face a unique dilemma regarding the issue of where to urinate, especially while traveling in a car. For example, individuals caught in traffic jams or snowstorms have limited options available for solving such a problem. Particularly in remote areas, public restrooms are often unavailable. Finding a secluded spot to urinate outdoors is often impossible. Even if such a place is located, the process is often uncomfortable, especially for women. For elderly or handicapped individuals, limited mobility may eliminate outdoor urination as an option.

[0004] Even if a restroom is available while traveling, people are often reluctant to use it because of concerns regarding sanitation. Growing fears of infection with the AIDS virus, Herpes, and many other microorganisms has made people more reluctant to expose themselves to unnecessary health risks. Many people are concerned about potential health hazards due to transmission of diseases from use of a public restroom. Although it is debatable as to whether these organisms remain infectious in such an environment, many individuals would prefer not to take this risk.

[0005] Moreover, when traveling in remote areas, using a public facility may involve a substantial safety risk for personal assault. This is particularly true for travel at night, especially for women and elderly individuals.

[0006] The alternative of holding the urine for extended periods of time while waiting to arrive at a suitable destination presents other undesirable problems. Apart from the obviously painful nature of such an option, the practice of delaying urination can result in medical problems for certain individuals who are at risk for bladder and

kidney infections. For people who suffer from urinary urgency, loss of sphincter control, and various other conditions, waiting to urinate may not be possible.

[0007] Another important use of a portable disposable urinary device is in medical settings, such as hospitals, nursing homes, and rehabilitation centers. Avoiding catheterization is preferable whenever possible. However, patients are often unable or reluctant to make a painful trip to the restroom or use a bedpan or urinal due to discomfort or weakness from a surgery or illness, or due to mobility constraints such as a wheelchair. Moreover, nursing home residents frequently do not want to wear disposable diaper products all day because of chaffing, odor, dignity, and discomfort.

[0008] Obviously, this problem is not new, and various attempts have been made to provide urination alternatives. None of these devices, however, have solved the problem of providing a portable, disposable, and hygienic urinary device that is easy to carry and use and inexpensive to manufacture.

[0009] Efforts to develop urinary devices have led to various designs as exemplified in the following patent disclosures.

[0010] U.S. Patent No. 4,457,314 issued on July 3, 1984 to **Knowles** claims a female urine collection device and method which includes a cup-shaped receiving chamber with a flexible lip which seals around the urethral orifice. A duct section leads to flexible tubing leading to a compressible collection reservoir. The chamber and reservoir are mounted in a housing of soft absorbent material.

[0011] U.S. Patent No. 5,678,564 issued on October 21, 1997 to **Lawrence et al.** describes a liquid removal system which utilizes a membranous interface device which maintains a vacuum on one side. The vacuum operates such that liquid passes through the membrane and is removed to a receptacle for disposal.

[0012] U.S. Patent No. 4,756,029 issued on July 12, 1988 to **Zieve et al.** describes a feminine urinary device which permits urinating in a standing position. The device has a hingedly attached flap with expandable walls which permit the side walls to expand downward in order to collect the urine. The pad is held in place against the body for the passage of urine into the expandable receptacle. Alternatively, the device can be designed to include an aperture which attaches to a spout which acts as a conduit for the urine.

[0013] U.S. Patent No. 4,781,713 issued on November 1, 1988 to **Welch et al.** describes a disposable incontinency pad for females which includes an absorbent

pad encased in a moisture resistant layer to prevent leakage. The device includes an ovoid opening with a contoured rim portion which conforms to the urinary area of the wearer. The rim directs urine into the pad and away from the user.

[0014] None of the inventions described above provide an easy to use, comfortable, disposable urinary device. Most of these designs present contact surfaces which are uncomfortable and ill-fitting. Some of these devices are also unwieldy to maneuver, especially for discrete disposable use in those areas where the necessity to use such a device is most likely to occur.

Summary of the Invention

[0015] Therefore, the primary object of the present invention, is a comfortable, hygienic urinary device which allows a person to urinate in a variety of positions without wetting clothing and body parts. Another object of the present invention is to provide a device which is convenient to carry, easy to use, and inexpensive to manufacture. Another object of the present invention is to provide a urinary device which is disposable and biodegradable. The present invention would provide a disposable urinary device which could be used in a variety of travel settings. Yet another object of this invention is a disposable urinary device for use in a medical or extended care setting, which could be administered by the patient or resident as well as by the attending nurse or caregiver.

[0016] The urinary device of the present invention is a self-contained disposable apparatus with an absorbent concave pad for the collection of urine. The design includes a glove which is attached to the absorbent pad which has a mitt for the user's hand to support the absorbent pad. The absorbent pad is composed of a waterproof liner, absorptive layers, and a protective moisture layer. This device can be used in a variety of positions, such as lying down on the side or back, sitting, or standing. The hand of the user is inserted into the mitt prior to urination and removed after urination by folding the sleeve of the glove over the top of the absorbent pad. The device may then be secured prior to disposal by a variety of methods, including a zipper top closure, twist tie, or drawstring feature, connected to the distal end of the sleeve.

[0017] The device includes an absorbent pad which contains several layers. The waterproof plastic liner on the bottom of the pad serves to contain the urine without leakage. The next layer is made of hydrophilic gel and absorbent materials.

Next, there are panels of absorbent material to direct and absorb the liquid. The top protective layer is fluid pervious to permit the entrance of urine into the absorptive layers. The rim of the absorbent pad forms a lip which is not only absorbent, but which provides a supportive contour to the device and a soft body-conforming surface to prevent leakage. The absorbent material on the top surface of the device may also be used to wipe away residual urine. An alternative embodiment of the device may also have a separate wipe which is included to wipe away residual urine.

Brief Description of the Drawings

[0018] **FIG. 1A** is a side view of the present invention illustrating the urinary device positioned on the hand of the user.

[0019] **FIG. 1B** is a side view of the present invention with the top protective layer of the urinary device lifted away from the rim of the absorbent pad for illustration.

[0020] **FIG. 2** is a top view of the present invention illustrating the urinary device positioned on the hand of the user.

[0021] **FIG. 3** is a bottom view of the present invention illustrating the urinary device positioned on the hand of the user.

[0022] **FIG. 4** is an illustration of the layers of the absorbent pad of the present invention. **FIG. 5A** is an illustration of the urinary device of the present invention.

[0023] **FIG. 5B** is an illustration of the urinary device of the present invention showing the glove partially turned inside out.

[0024] **FIG. 5C** is an illustration of the urinary device of the present invention showing the glove turned inside out almost completely covering the absorbent pad.

[0025] **FIG. 5D** is an illustration of the urinary device of the present invention showing the glove turned fully inside out around the absorbent pad.

[0026] **FIG. 6A** is a top view illustration of the absorbent pad of the present invention showing the embodiment with a series of straight panels.

[0027] **FIG. 6B** is an illustration of the straight panel embodiment of the present invention.

[0028] **FIG. 7A** is a top view illustration of the absorbent pad of the present invention showing the embodiment with a series of boxed panels.

[0029] **FIG. 7B** is an illustration of the boxed panel embodiment of the present invention.

[0030] **FIG. 8A** is a top view illustration of the absorbent pad of the present invention showing the embodiment with a series of circular panels.

[0031] **FIG. 8B** is an illustration of the circular panel embodiment of the present invention.

[0032] **FIG. 9A** is a top view illustration of the absorbent pad of the present invention showing the embodiment with a series of honeycombed panels.

[0033] **FIG. 9B** is an illustration of the honeycombed panel embodiment of the present invention.

[0034] **FIG. 10A** is an illustration of the twist tie closure embodiment of the present invention.

[0035] **FIG. 10B** is an illustration of the drawstring closure embodiment of the present invention.

[0036] **FIG. 10C** is an illustration of the plastic zipper closure embodiment of the present invention.

[0037] **FIG. 11** is an illustration of the absorbent pad of the urinary device of the present invention positioned for use.

[0038] **FIG. 12** is a perspective view of an alternate preferred embodiment of the present invention.

[0039] **FIG. 13** is a cross sectional view of the alternate preferred embodiment of the present invention shown in **FIG. 12**.

[0040] **FIG. 14** is a cross sectional view of a further alternate preferred embodiment of the present invention.

[0041] **FIG. 15** is an exploded view of the component elements of a kit embodiment of the present invention.

[0042] **FIG. 16** is a perspective view of an alternative shape for the present invention.

Description of the Preferred Embodiments

[0043] Reference is made first to **FIG. 1A** for an overview of the urinary device **10** of the present invention. As shown in **FIG. 1A**, the device is an absorbent pad **30** attached to a waterproof glove **20**. The hand **40** of the user is inserted into the sleeve **22** of the waterproof glove **20** such that the hand **40** is in the mitt **21** of the

waterproof glove 20 supporting the absorbent pad 30. The absorbent pad 30 has a waterproof lining 80, a rim 60, panels of absorbent material 70, and a top protective layer 100. This top protective layer 100 is shown in a raised position in FIG. 1B to illustrate its attachment to the rim 60 of the absorbent pad 30 as a thin, permeable covering. As shown in FIG. 3, the absorbent pad 30 is preferably constructed such that the shape of the bottom of the pad 30 fits the contour of the hand of the user 40. The rim 60 of the absorbent pad 30 is configured to easily align with the contours of the body, both for comfort and to form a seal when in use.

[0044] Continuing, FIG. 2 illustrates the top view of the present invention, showing the panels 70, rim 60, and top protective layer 100 of the absorbent pad 30. As shown in FIG. 4, the absorbent pad 30 is composed of several layers. The bottom layer forms a shell of waterproof lining 80 composed of materials well known in the art such as impervious polyethylene or polypropylene film or thermoplastic polymer to hold the urine within the urinary device 10. The next layer is composed of layers of hydrophilic gel and absorbent materials 90. The hydrophilic gel is made of super-absorbent polymer particles which contain water-absorbing resins that are well known in the art.

[0045] FIG. 4 illustrates the panels 70 which are positioned above the hydrophilic gel and absorbent material layer 90 in the absorbent pad 30. These panels 70 are composed of a non-woven sponge-like material or bonded-fiber fabric layers. In one embodiment, the panels 70 are formed of a non-woven material composed of a cellulose and synthetic fiber blend which is well known in the art. The panels 70 may be configured in various shapes, as is shown in FIGS. 6A, 6B, 7A, 7B, 8A, 8B, 9A, and 9B. FIGS. 6A and 6B illustrate the straight configuration 72 of the panels 70 in which they are constructed and arranged lengthwise across the ovoid absorbent pad 30. FIGS. 7A and 7B show the boxed configuration 74 of the panels 70 in which they are rectangularly arranged within the absorbent pad 30. FIGS. 8A and 8B reveal a circular arrangement 76 of the panels 70, in which they are concentrically positioned within the absorbent pad 30. FIGS. 8A and 8B illustrate the honeycombed configuration 78 of the panels 70, in which they are arranged in a lattice type formation within the absorbent pad 30.

[0046] Returning to FIG. 4, the next layer in the absorbent pad 30 is the top protective layer 100, which is designed to allow fluids to enter the surface of the absorbent pad 30. This top protective layer is composed of a hydrophilic, fluid

pervious, fibrous, non-woven web well known in the art. This layer provides suitable fluid handling capabilities and desirable tactile softness. Other suitable materials known in the art that would also be appropriate include a liquid-pervious cover layer against which individual hydrophobic fibers are arranged. The cover layer contains fiber-free regions to promote liquid transfer through the cover layer. Such an external cover layer is user-friendly as it is both soft and exhibits a dry surface after wetting.

[0047] Reference is now made to the rim of the absorbent pad which is illustrated in **FIG. 4**. The rim forms the lip of the absorbent pad, functioning to shape the pad, prevent leakage, and absorb residual moisture during use. The rim is composed of a soft, absorbent cord constructed from woven fibers.

[0048] Continuing in **FIG. 5A**, the urinary device of the present invention is shown after removal from the hand of the user. **FIG. 5B** illustrates the manner in which the sleeve of the waterproof glove of the urinary device is turned back upon itself as the initial step in covering and disposing of the used article. **FIG. 5C** shows the urinary device with the absorbent pad almost entirely covered by the inverted sleeve. Finally, in **FIG. 5D**, the urinary device is illustrated with the absorbent pad completely hidden inside the inverted sleeve. The embodiment of **FIG. 5D** has a zipper closure feature (also depicted in **FIG. 10C**) at the distal end of the sleeve for sealing the absorbent pad within the waterproof glove of the urinary device in preparation for disposal.

[0049] Alternative closure methods are illustrated in **FIGS. 10A** and **10B**. **FIG. 10A** shows a twist tie feature located at the distal end of the sleeve of the urinary device. **FIG. 10B** reveals a drawstring closure design at the distal end of the sleeve of the urinary device.

[0050] Actual use of the urinary device 10 requires inserting the user's hand 40 into the sleeve 22 and mitt 21 of the waterproof glove 20 to cradle the bottom 50 of the absorbent pad 30 (see **FIG. 1A**). Next, as shown in **FIG. 11**, the absorbent pad 30 of the urinary device 10 is positioned against the urinary area in such a manner that the user is able to direct the flow of urine into the panels 70 of the absorbent pad 30. After voiding, the user can slide the urinary device 10 forward such that the rim 60 of the absorbent pad 30 absorbs any residual urine present on the body of the user. Alternatively, a disposable wipe may be provided with the device for removal of residual urine.

[0051] Reference is now made to **FIGS. 12 and 13** for a brief description of an alternate embodiment of the present invention. **FIG. 12** is a prospective view of a configuration of the present invention showing urinary device **110** positioned and affixed to a closure sleeve that is easier to manufacture than in the first described embodiment (**FIGS. 1A and 1B**), but which still maintains most of the functionality required for holding and enclosing the urinary device. As indicated, urinary device **110** is positioned on and adhered to an absorbent sheet **112** that itself is positioned on and adhered to a plastic bag enclosure **114**. Bag enclosure **114** may preferably be constructed of a polyethylene material that is light weight, strong, but inexpensive to manufacture. In the present application wherein the enclosure bag **114** serves to hold and eventually enclose urinary device **110** the closure means comprises a pair of bag extensions or "ears" **116A** and **116B**.

[0052] Use of the device shown in **FIG. 12** is essentially the same as the use of the first preferred embodiment described above. The user inserts a hand into enclosure bag **114** and holds urinary device **110** through the surface of bag **114** and absorbent pad **112**. Absorbent pad **112** serves to provide both comfort to the user and a means for absorbing any leakage or over spill from the urinary device **110**.

[0053] After use, the user turns the bag enclosure **114** over urinary device **110** and absorbent pad **112** so as to fully enclose them within the waterproof bag. The user then ties together bag extensions **116A** and **116B** to form a disposable unit.

[0054] **FIG. 13** shows a side view of the embodiment disclosed and described in **FIG. 12**. In this view, adhesive material **118** is shown positioned to secure absorbent pad **112** to an upper surface of bag enclosure **114**. Bag opening **120** is shown as it would be positioned to receive the user's hand for use of the urinary device **110**.

[0055] Reference is finally made to **FIG. 14** for a brief description of a third embodiment of the present invention which comprises a slight modification of the embodiment shown in **FIGS. 12 and 13**. Instead of being fully enclosed as shown in **FIGS. 12 and 13**, an alternate configuration of urinary device **130** is shown in cross section. In this view it can be seen that an aperture **142** exists in a lower portion of urinary device **130** beneath the absorbent material therein. Urinary device **130** is, as shown in **FIGS. 12 and 13**, positioned on and adhered to absorbent pad **132** which itself is positioned on and adhered to a waterproof lining **134**. Waterproof lining is itself sealed at its edge to enclosure bag **136**. Waterproof lining **134** and absorbent

pad 132 also define portals aligned with the portal and the base of urinary device 130. These portals allow excess fluid not absorbed by the absorbent material within urinary device 130 to flow through portal 142 and into a secondary layer of absorbent material 138. All of absorbent material 138 is fully retained between enclosure bag 136 and waterproof lining 134. The only access into this enclosure to absorbent material 138 is through the portals 142 aligned as shown. Use of the embodiment shown in FIG. 14 is the same as that described above with respect to the embodiment disclosed in FIGS. 12 and 13.

[0056] The user then inverts the sleeve 22 of the waterproof glove 20 such that the sleeve 22 completely envelopes the absorbent pad 30 (see FIG. 5D). The user can then seal the closure at the distal end 23 of the sleeve 22 and dispose of the urinary device 10. Alternative embodiments of the urinary device 10 include the absorbent pad 30 without the attached glove 20, either with or without a disposal means, such as a pouch or bag. In an alternative embodiment, the urinary device of the present invention may be manufactured with a deodorizing substance contained within the absorbent pad in order to reduce or eliminate odors. In a medical setting, when fluid intake and output measurement is important, the device may be weighed to determine the quantity of urine excreted, similar to the weighing of diapers in a hospital nursery. The urinary device of the present invention may be designed to accommodate persons of varying size and age. For example, a small device may be most useful for children, providing a better fit and adequate urinary capacity.

[0057] Reference is now made to FIG. 15 for a brief description of the components of a kit that would include the absorbent pad of the present invention. The kit shown is comprised of four main elements that include the absorbent pad, a small wipe pad, a thin lap cover, and the envelope package enclosure. The small wipe pad is provided to the user for cleanliness after use of the product. The wipe pad may be either a soft absorbent material such as a paper tissue or may be a stronger fiber based material that is moistened with antibacterial substances and/or moistening substances. If the wipe is of the moist type, it would be separately enclosed in a thin wrapping to prevent the moisture from escaping into the absorbent pad. If the wipe pad is of the dry type, it could be placed directly on top of the absorbent pad of the present invention within the kit shown in FIG. 15.

[0058] The lap cover shown in FIG. 15 is a generally rectangular sheet of paper based material that is folded into a convenient size to be included in the kit.

The purpose of the lap cover is to provide some privacy to the user during use of the product in such instances where the location of the use of the product demands if necessary the user of the product may unfold the lap cover and extend it over their abdominal area so as to visually hide their use of the product. It is not anticipated that every situation would demand the use of the lap cover of the kit shown. Single item sales of the product would likely include a lap cover whereas packages that incorporated multiple items of the product may preferably include one lap cover for every three items of the product.

[0059] Finally, all three of the packaged components of the kit shown in **FIG. 15** would be placed together and inserted into a pliable plastic envelope having a means for sealing the envelope once the kit product components are included inside. The pliable plastic could be heat sealed or may retain an adhesive seal in a manner that is well known in the art.

[0060] Although the present invention has been described as being configured to easily align with the contours of the body, a slight modification of the above design may be ergonomically preferable. **FIG. 16** discloses such a modified structural shape that provides for a narrower front facing portion and a wider portion in the back. Construction of such a shape can be easily accomplished using the known manufacturing procedures that cut, shape, tuft and gather the various materials of construction of the present invention into the intended configuration. The structure shown in **FIG. 16** provides both user comfort and a wider opening into the absorbent material of the present invention to insure full coverage. The narrower front section continues to provide an adequate opening for proper receipt of fluids into the absorbent material but at the same time provides a more comfortable sized product to be positioned as shown in **FIG. 11** described above.

[0061] Although the present invention has been described in conjunction with certain preferred embodiments and certain specific applications, it is anticipated that those skilled in the art will discern further embodiments and applications that fall within the scope of the invention and the following appended claims.